



# Dr. Sonic 160 - Med 160



IDEALI PER FORNIRE ARIA COMPRESSA A 2 RIUNITI.  
 IDEAL TO DELIVER COMPRESSED AIR TO 2 DENTAL CHAIRS.

- Serbatoio da 24 litri, con protezione interna anti-ossidazione.
- Ventola ad alta portata convogliata per un facile raffreddamento.
- Interruttore on-off.
- Cavo con spina Plug-and-Play.
- Elettrovalvola "secure starting".
- Filtro uscita aria.
- Antivibranti serbatoio a ventosa per una perfetta installazione.
- Doppio manico per una facile movimentazione.
- Protezione termica del motore.
- Versione silenziosa "Dr Sonic" con carenatura insonorizzante ed essiccatore.
- Versione "Med" completabile con cabina fonoassorbente ed essiccatore.

- 24-lt tank, with inner anti-oxidant coating.
- High-capacity fan and forced air system for improved cooling.
- On-off switch.
- Cable with Plug-and-Play socket.
- "Secure starting" solenoid valve.
- Air outlet filter.
- Tank vibration pads, with suction cups for a safer installation.
- Double handle for easier handling.
- Motor thermal cut-out.
- "Dr Sonic" silenced version with soundproofing casing and drier.
- "Med" version completable with dryer and sound-proofed casing cover.



Dr. Sonic 160-24F-ES-1,5M



56 dB(A)



Med 160-24F-1,5M

	Codice Code	Prodotto Product	Vcl/Ph	W	HP	Model	I/min.	m <sup>3</sup> /h	c.f.m.	bar	p.s.i.	R.P.M.	n°	n°	dB(A)	L x D x H (cm)	kg	lbs
24	669QT4A604	Dr. Sonic 160-24F-ES-1,5M	230/1	1100	1,5	MK160	115	6,9	4	8	116	1420	1	1	56	67 x 50 x 75	56	123.5
24	669QT1A604	Med 160-24F-1,5M	230/1	1100	1,5	MK160	115	6,9	4	8	116	1420	1	1	69	58 x 50 x 71	37,5	82.7

Versioni con diverse tensioni e/o frequenze disponibili a richiesta.  
 Versions featuring different voltage and/or frequency ratings are available on request.